

AXIAL FLOW FAN

Description:

These axial flow fans play an important role wherever dust, steam or heat are a problem in any type of industry. All units are standard with an IP55 motor, however additional dust and/or water protection are available upon request. Flanges are pre-drilled for bolting into existing duct work.

Features:

- ⊕ Suitable for extracting dust, fumes & smoke from a room to the outside
- ⊕ Used in spray booths or heat and steam extraction
- ⊕ Intrinsically safe models available on sizes starting from 400mm
- ⊕ Models with "E" suffix are intrinsically safe



Specifications:

Model #	Diameter	Motor	Air Flow
AF3-370-4	300mm	370W/240v	680L/s
AF3-370-4-3	300mm	370W/415v	680L/s
AF3-550-2	300mm	550W/240v	
AF3-550-2-3	300mm	550W/415v	
AF3-750-2	300mm	750W/240v	1400L/s
AF3-750-2-3	300mm	750W/415v	1400L/s
AF4-370-4	400mm	370W/240v	1500L/s
AF4-370-4-3	400mm	370W/415v	1500L/s
AF4-370-4-3E	400mm	370W/415v	1500L/s
AF5-11-2	500mm	1100W/240v	
AF5-11-2-3	500mm	1100W/415v	
AF5-11-2-3-E	500mm	1100W/415v	
AF5-750-4	500mm	750W/240v	2700L/s
AF5-750-4-3	500mm	750W/415v	2700L/s
AF5-750-4-3E	500mm	750W/415v	2700L/s
AF6-11-4	600mm	1100W/240v	3800L/s
AF6-11-4-3	600mm	1100W/415v	3800L/s
AF6-11-4-3E	600mm	1100W/415v	3800L/s
AF6-15-4	600mm	1500W/240v	
AF6-15-4-3	600mm	1500W/414v	
AF8-15-4-3	800mm	1500W/415v	6000L/s
AF8-22-4-3	800mm	2200W/415v	8000L/s
AF10-55-6-3	1000mm	5500W/415v	12000L/s

