

# MINI MANCOOLER

## Description:

The Fanmaster Mini Mancoolers are manufactured in our warehouse with quality parts and design. These units come standard with IP55 rated motors (higher ratings and intrinsically safe available) and ducting can be fitted for confined space usage. The Mini Mancoolers are best suited in factory situations and are capable of extracting dust, fumes and smoke from these environments. The Mini Mancooler fans offer a flexible and compact form of air extraction and ventilation by quickly lowering the temperature, or by directing cool air over workers in hot working areas. The Mini Mancoolers are available in both 300mm or 400mm diameter and are capable of being wall mounted.



## Features:

- ⊕ Australian made and robustly built
- ⊕ Extracts dust, fumes and smoke
- ⊕ Can be fitted with ducting
- ⊕ Available as wall mounted or portable
- ⊕ Allows vertical tilt adjustment & easy portability
- ⊕ Intrinsically safe (Ex e motors) models available on sizes starting from 400mm

## Specifications:

Model #	Diameter	Motor	Pole	Voltage	Plug	Air Flow	Weight
MC3-370-4	300mm	370W	4	240	3 Pin 10a	600L/s	25kg
MC3-370-4-3	300mm	370W	4	415	4 Pin 10a	600L/s	25kg
MC3-550-2	300mm	550W	2	240	3 Pin 10a	1140L/s	27kg
MC3-550-2-3	300mm	550W	2	415	4 Pin 10a	1140L/s	27kg
MC4-370-4	400mm	370W	4	240	3 Pin 10a	1250L/s	30kg
MC4-370-4-3	400mm	370W	4	415	4 Pin 10a	1250L/s	30kg
MC4-750-2	400mm	750W	2	240	3 Pin 10a	2120L/s	35kg
MC4-750-2-3	400mm	750W	2	415	4 Pin 10a	2120L/s	35kg

Air flow stated is free air flow. Intrinsically safe refers to motor Ex e.



**FANMASTER**  
COOLING HEATING VENTILATION EXTRACTION