

# MOBILE MANCOOLER

## Description:

The Mobile Mancooler is a heavy duty Australian made fan which circulates & extracts air. The Mobile Mancooler is available in single and 3-phase models and also as an optional intrinsically safe motor model. The Mobile Mancooler is currently used extensively in a wide range of industries. They can be used to circulate air in a factory environment or be used to evacuate smoke, fumes or dust from a work place. Available in a range of sizes to suit various needs.

## Features:

- ⊕ Circulate air to workers in enclosed or hot locations
- ⊕ Extracts dust, fumes and smoke
- ⊕ Intrinsically safe models available upon request
- ⊕ Low wattage means cheaper running costs
- ⊕ Portable and easy-to-use



## Specifications:

Model #	Diameter	Motor	Pole	Voltage	Plug	Air Flow
MC5-750-4	500mm	750W	4	240	3 Pin 10α	2600L/s
MC5-750-4-3	500mm	750W	4	415	3 Pin 10α	2600L/s
MC5-11-2	500mm	1100W	2	240	3 Pin 10α	3450L/s
MC5-11-2-3	500mm	1100W	2	415	3 Pin 10α	3450L/s
MC6-750-4	600mm	750W	4	240	3 Pin 10α	3900L/s
MC6-750-4-3	600mm	750W	4	415	3 Pin 10α	3900L/s
MC6-750-4-3-E	600mm	750W	4	400	3 Pin 10α	3900L/s
MC6-11-4	600mm	1100W	4	240	3 Pin 10α	4500L/s
MC6-11-4-3	600mm	1100W	4	415	3 Pin 10α	4500L/s
MC6-15-4	600mm	1500W	4	240	3 Pin 10α	5250L/s
MC6-15-4-3	600mm	1500W	4	415	3 Pin 10α	5250L/s
MC6-15-4-3E	600mm	1500W	4	400	3 Pin 10α	5250L/s
MC8-15-4	800mm	1500W	4	240	3 Pin 10α	6800L/s
MC8-15-4-3	800mm	1500W	4	415	3 Pin 10α	6800L/s
MC8-22-4	800mm	2200W	4	240	3 Pin 10α	8820L/s
MC8-22-4-3	800mm	2200W	4	415	3 Pin 10α	8820L/s
MC10-3-4-3	1000mm	3000W	4	415	3 Pin 10α	
MC10-55-6-3	1000mm	5500W	6	415	3 Pin 10α	17000L/s

*Air flow stated is free air flow. Intrinsically safe refers to motor Ex e.*



**FANMASTER**  
COOLING HEATING VENTILATION EXTRACTION