

Portable Electric Space Heater

FAB SHEET

FEATURES

- ✓ Available in 3 sizes
- ✓ Safety cut-off switch
- ✓ Adjustable thermostat
- ✓ Multiple heat settings
- ✓ Fan only option
- ✓ Run on fan timer
- ✓ Adjustable airflow direction
- ✓ Portable with wheels (PESH15/30)
- ✓ Portable with handle (PESH9)

ADVANTAGES

- ✓ Allows for correct heater selection
- ✓ Increased safety measures
- ✓ Ability to control the temperature
- ✓ Reduced power and running cost
- ✓ Can be used as a fan only
- ✓ Ensures elements are cooled down
- ✓ Ability to direct airflow where required
- ✓ Easy to move and relocate
- ✓ Easy to move and relocate

BENEFITS

- ✓ Multiple applications
- ✓ Reduced risk of hazards
- ✓ Controlled heating
- ✓ Saves money
- ✓ Versatile
- ✓ Reduced risk of hazards
- ✓ Multiple applications
- ✓ Ability to move to specific work areas
- ✓ Ability to move to specific work areas



PESH9



PESH15



PESH30

Applications:

- ☉ Warehouses
- ☉ Workshops
- ☉ Factories
- ☉ Agricultural
- ☉ Drying
- ☉ Events (tents/marques)
- ☉ Load bank testing
- ☉ Be used where the naked flame of a gas or diesel fired heaters cannot be used.

Portable Electric Space Heater

TECHNICAL DATA SHEET

SPECIFICATION

Model No	PESH9	PESH15	PESH30
Power	52W/4.5kW/9kW	95W/5kW/10kW/15KW	170W/15kW/30kW
Voltage	415V / 50Hz	415V / 50Hz	415V / 50Hz
Plug Connection	5 pin 20amp	5 pin 32amp	5 pin 50amp
Current (A)	12.52	20.82	41.74
Safety Cut-off switch	Yes	Yes	Yes
Run-on timer function (fan)	Yes	Yes	Yes
Manual reset	Yes	Yes	-
Heater Type	Electric fan forced - coiled elements	Electric fan forced - coiled elements	Electric fan forced - coiled elements
Material	Rolled Steel	Rolled Steel	Rolled Steel
IP Rating	IP24	IP24	IP24
Airflow (L/s)	132	261	400
Measurements (mm)	393(L)x395(D)x563(H)	514(L)x541(D)x869(H)	652(L)x617(D)x1018(H)
Weight (kg)	10.7	20	30
Settings	1 - fan 2 - heat	1 - fan 3 - heat	1 - fan 2 - heat
Angle adjustment	20°	20°	20°
Cable length	1.8m	3.0m	3.0m

* The PESH range is designed and to be used for 'Industrial use only'